25 Night VFR Rating

The aim of this flight test is for the applicant to demonstrate competency in the knowledge, skills and attitudes as required in Schedule 5 of the Part 61 MOS for the grant of the night VFR rating (NVFR).

25.1 Examiner requirements

The following examiner requirements are applicable to the conduct of the NVFR flight test:

- (1) The examiner must conduct the NVFR flight test in accordance with clauses 1 to 3 of Schedule 5 of the Part 61 MOS.
- (2) The examiner must conduct the NVFR flight test within the operational scope and conditions described in clause 4 of Schedule 5 of the Part 61 MOS.
- (3) The examiner must ensure that the ground component of the flight test is successfully completed before conducting the pre-flight briefing and flight component of the flight test.
- (4) The examiner must not introduce simultaneous, multiple and unrelated simulated emergencies or abnormal events during the flight. Emergencies and abnormal situations relating to aircraft systems, powerplants and the airframe must be limited to those described in the AFM.
- (5) After a simulated failure, the examiner must ensure the aircraft is reconfigured to a normal operating mode before another simulated failure may be introduced, except where the simulated failures are linked. The safety of the aircraft should never be in doubt when simulating emergencies or failures.
- (6) Where credits are available for flight test items, they are valid for 28 days only. After 28 days, the flight test must be conducted in full.

25.2 Plan

25.2.1 Testing methodology

The examiner should apply the flight test methodology described in chapter 3, Adult education and competency based assessment and chapter 4, Assessment of human factors and non-technical skills.

The flight test should be designed such that all required components can be assessed in a logical sequence. Where one or more mandatory units or elements are unable to be assessed for any reason, the flight test cannot be completed.

The examiner must ensure the applicant is given adequate notice of the intended navigation task to allow for unhurried preparation and planning (simulating a private or commercial operation as applicable to the licence the applicant holds). The applicant should be given the test route at least 24 hours before the start of the flight test.

It is recommended that the examiner plans an **airborne** time of approximately:

 1.5 hours for the navigation task (this should not include time delays which may be experienced at a busy Class C or D airport) 0.8 hour for the general handling and test specific manoeuvres.

Use of IFR procedures

If IFR procedures are used for a positioning flight, this part of the flight should not form part of the flight test or be taken into account in the flight test flight time. A landing and shutdown should terminate the IFR flight segment before commencing the NVFR assessment flight sequences.

The NVFR flight test should be concluded by a landing and shutdown in VFR conditions before commencing the IFR return positioning flight.

Only the flight time associated with the NVFR flight test should be considered as the flight time for the flight test.

If the NVFR applicant holds a valid IR and elects to convert to IFR during the NVFR assessment flight, then a fail assessment should be recorded and no NVFR flight component test credits are to be given.

25.2.2 NVFR assessment scope and conditions

The NVFR flight test must be conducted by night under the VFR and in an aircraft or an FSTD approved for the purpose, in accordance with subregulation 61.975 (2) of CASR.

The aircraft and FSTD used for the NVFR flight test must be of the appropriate category and be capable of being operated for the kind of operations relevant to the night VFR endorsement(s) covered by the flight test.

The FEH activities and manoeuvres, listed in the Requirements column of Table 27 below, mirror the NVFR test form and FTM items. They are a paraphrase of the Part 61 MOS Schedule 5 for the NVFR flight test.

These activities and manoeuvres, described in clause 3 of Schedule 5 of the MOS and the NVFR test form, must be assessed against a representative sample of the performance criteria applicable to the Element being assessed, taking into account the relevant competency standards prescribed in Schedule 2 of the MOS.

NVFR flight tolerances and ground reference tolerances are specified in Tables 1 and 3 of Schedule 8 of the MOS. Sustained deviation outside the applicable flight tolerance is not permitted.

The NVFR applicant should demonstrate that control of the aircraft or procedure is maintained at all times but if the successful outcome is in doubt, corrective action is taken promptly to recover to safe flight.

Where the aircraft is fitted with an autopilot system, the applicant must demonstrate competency in the system. If an auto-pilot is not available, the examiner must not 'act' as the auto-pilot.

The examiner must ensure that the navigation and circuit components of the flight test are conducted by night under the VFR.

For ME aircraft, a simulated engine failure in the cruise at night must be conducted not below the route LSALT.

In an aircraft, recoveries from unusual attitudes must be conducted by day in VMC.

For the above procedures the concept is that the examiner has a clear view of the horizon.

For a flight test that is for the grant of an additional Night VFR endorsement, the applicant must demonstrate competency by performing all the activities and manoeuvres described on the NVFR flight test form.

25.3 Conduct (ground component)

25.3.1 Initial brief to applicant

In accordance with chapter 3, Adult education and competency based assessment; the examiner must begin the flight test with a brief to the applicant on the following items:

- flight test context, purpose and content
- assessment procedure
- function of the examiner
- standards against which competency will be assessed
- actions in the event of a failure assessment.

The applicant should be encouraged to ask for clarification should they become uncertain on any of the flight test elements.

25.3.2 Document review

The examiner must confirm that an applicant for the NVFR satisfies the eligibility requirements to undertake the flight test for the grant of the night VFR rating. To achieve this, the CASR 61.235 (4) certification, training records, logbook, licence and medical certificate must be checked. Ideally, these documents should be presented to the examiner prior to the commencement of the flight test.

Licence – the applicant for the NVFR must hold a PPL, CPL or ATPL (or be applying for the licence simultaneously with the NVFR) of the same category as the aircraft in which the flight test is conducted.

Aeronautical knowledge examinations – N/A

Knowledge deficiency report (KDR) – N/A

Flight training requirements – the examiner must review the applicant's pilot training records to ensure that the training requirements have been met. Normal evidence should at least be a course completion certificate.

Aeronautical experience – the examiner must review the applicant's pilot logbook to ensure that the minimum aeronautical experience requirements have been met.

English language proficiency – N/A

Eligibility certification – the examiner must ensure that an appropriate person of the training provider has certified in writing that the applicant is eligible to take the flight test.

Medical certificate – for flight tests conducted in an aircraft, the examiner must check that the applicant holds either a class 1 or 2 medical certificate, or a medical exemption allowing them to exercise the privileges of the NVFR.

Security check and fit and proper person requirements – N/A

If the flight test is a retest following a fail assessment – the examiner must review the applicant's training records for evidence that appropriate remedial training has been successfully carried out with the applicant.

25.3.3 Assessment of knowledge requirements

Questions for the oral knowledge assessment must be in accordance with the knowledge requirements topics listed in clause 2 of Schedule 5 of the Part 61 MOS.

The examiner should use a developed set of scenario-based questions for the listed topics to achieve effective assessment of the applicant's working knowledge and reasoning ability. It should be a structured conversation to a logical conclusion, starting broad and funnelling down, rather than simple factual recall. Refer to FEH 3.2.5 - 3.2.7 for appropriate questioning techniques and methods of enquiry.

25.3.4 Assessment of flight planning

As part of the flight test, the applicant must complete a:

- flight plan
- fuel plan
- flight notification
- weight and balance calculation
- take-off and landing distance/performance calculation.

When reviewing the applicant's flight preparation documents, the examiner must be satisfied that the applicant is able to validate the data on which the planning decisions and calculations have been made (including, forecast weather, NOTAMs, aircraft data, chart validity).

The examiner must ensure, through considered questioning, that the preparation is solely the work of the applicant and meets the knowledge standards as applicable.

25.4 Conduct (flight component)

25.4.1 Assessment of the applicant's performance

The applicant's performance is assessed for technique, judgement, knowledge, smoothness, accuracy, procedures and flight management. The following explanations are provided to assist the examiner in assessing the flight component:

- **Technique** the method by which a task is performed. There may be more than one acceptable technique and the examiner should be flexible in their assessment
- **Judgement** is applicable to all tasks but is of particular importance in respect of environmental conditions and effects such as cloud, wind and turbulence
- Knowledge during the course of the flight test the applicant's knowledge may be further tested
- Smoothness the applicant should demonstrate smooth flying in all sequences.
 Anything less is unacceptable and should result in a fail assessment.
- Accuracy accuracy in the control of height, airspeed, direction, balance and trim are all important. Persistent errors in any of these aspects should result in a fail assessment

- Procedures the applicant should demonstrate awareness and practical application of nominated standard operating procedures throughout the flight test
- **Flight management** the applicant should demonstrate satisfactory proficiency in aircraft and flight management systems, situational awareness, threat and error management and decision-making during the flight.

Assessment should be based on the technique used by the applicant and not just the ability to perform the task within specified numerical tolerances. Technique involves smooth and accurate control application in adjusting power, attitude, trim and balance in a timely and coordinated fashion whilst following correct procedures.

It may be that on some occasions the flight conditions are such that even though the applicant's technique is sound, the aircraft may deviate outside specified tolerances for short periods. In such cases the assessment of technique and judgment should be the determining factors.

Applicants should not be given a second opportunity to demonstrate a manoeuvre unless, in the opinion of the examiner, the circumstances causing failure of the first attempt were outside the control of the applicant in the test environment or the applicant recognised the error and self-managed corrective actions. This should be considered in relation to safety critical items where the applicant is demonstrating NTS2 TEM appropriately.

25.4.2 Pre-flight briefing

In accordance with chapter 3, Adult education and competency based assessment; the examiner must brief the applicant on:

- the scenario applied to the test environment (e.g. passenger carrying private or commercial operation / simulation of passengers)
- pilot in command
- transfer of control
- flight tolerances and ground references
- simulating emergencies, methods and calls
- actual emergencies
- procedures for simulating IMC.
- multiple flights and the assessment of competencies (if applicable).

The applicant should be encouraged to ask for clarification should they be uncertain about any of the briefed items.

25.4.3 Assessment of activities and manoeuvres

An examiner must comply with the requirements and take into account the recommendations described below when planning and conducting the **NVFR** flight test. Where there are no specific recommendations, 'NSR' is listed in the table against the unit or element.

Table 35: Assessment of activities and manoeuvres - NVFR

Phase of Flight	Requirements	Recommendations
Pre-flight	(a) Plan a night VFR flight	NSR
	(b) Perform pre-flight actions and procedures	NSR
Ground operations, take- off, departure and climb	(a) Complete all relevant checks and procedures	NSR
	(b) Plan, brief and conduct take-off and departure procedures	NSR
	(c) Conduct take-off and departure from aerodrome remote from ground lighting	Class D capital city airports are unsuitable for this assessment. If applicable, an intermediate airport remote from ground lighting should be planned.
En route cruise	(a) Navigate aircraft en route using visual tracking and visual position fixes	The navigation task should be designed such that all of the components can be assessed in a logical sequence. There should be at least one sector of sufficient distance that allows the applicant's navigation technique to be adequately assessed. This sector should be of a sufficient duration to enable the opportunity to assess multiple navigation cycles, track correction techniques, continued maintenance of navigation and fuel logs (ETAs and fuel status) and position fixing at suitable intervals.
		Importantly, examiners should be satisfied that the applicant is using a suitable navigation methodology that is supported by sound reasoning and application of recognised NVFR navigation procedures.
	(b) Navigate aircraft en route using ground and satellite navigation systems	NSR
	(c) Perform navigation systems integrity checks	NSR
	(d) Identify and avoid hazardous weather conditions	Verbal scenario(s) may be introduced if hazardous conditions are not present.

Phase of Flight	Requirements	Recommendations
Test specific activities and manoeuvres	(a) Perform full and limited panel instrument flying	For the limited panel assessment, the primary attitude indicator/display and the primary heading indicator/display may be 'failed' simultaneously. If assessed, unreliable airspeed indications must be a separate exercise. For EFIS cockpits, the use of standby instruments is acceptable for limited panel assessments.
	(b) Full and limited panel instrument flying, recover from at least 2 unusual	The unusual attitude recoveries must be conducted by day in VMC and the examiner should have visual reference at all times during the manoeuvre. At least one recovery full panel and at least one
	attitudes (c) Manage a cockpit	recovery limited panel must be assessed. NSR
	lighting failure	
	(d)&(e) For ME end, manage an engine failure during cruise	The one engine inoperative (OEI) assessment must be conducted not below the route LSALT.
Descent and arrival	(a) Conduct a descent and visual approach procedure to an aerodrome	NSR
	(b) Plan and conduct arrival and circuit joining procedures	NSR
Circuit, approach and landing	(a) Conduct normal circuit pattern, approach and landing	NSR
	(b) Conduct approach and landing to aerodrome remote from ground lighting	Class D capital city airports are unsuitable for this assessment. If applicable, an intermediate airport remote from ground lighting should be planned.
	(c) Land with and without landing lights	NSR
	(d) Perform a go- around procedure	NSR
	(e) Perform after- landing actions and procedures	NSR
Shut down and post-flight	(a) Park, shut down, secure aircraft and complete post-flight administration	NSR

Phase of Flight	Requirements	Recommendations
General requirements	(a) Maintain effective lookout	In most flight tests, the assessment of emergency and non-normal events will provide sufficient evidence of the NTS competencies. The examiner should provide, where possible, applicable operational environment scenarios to support these events. The examiner should request a copy of company SOPs to ensure familiarity with standard briefs, work-cycles and procedural techniques.
	(b) Maintain situational awareness	
	(c) Assess situations and make decisions	
	(d) Set priorities and manage tasks	
	(e) Maintain effective communications and interpersonal relationships	
	(f) Recognise and manage threats	
	(g) Recognise and manage errors	
	(h) Recognise and manage undesired aircraft state	
	(i) Use correct radio procedures	NSR
	(j) Manage relevant aircraft systems	NSR
	(k) Manage fuel system and monitor fuel plan and usage	NSR

25.4.4 Failure assessment

The failure to perform a manoeuvre or procedure may be broken into two levels depending on the safety implications during the flight test. Both levels result in a fail assessment.

Safety critical items

The highest level, being safety critical, is where the control of the aircraft is such that the safe outcome of the manoeuvre or procedure is in doubt and the examiner has to take control (physically or by direction).

Examples of safety critical failure items include, **but are not limited to**:

- failure to complete checklist items mandated by the AFM
- failure to correctly prepare the aircraft for flight
- failure to comply with ATC clearances and airspace requirements
- failure to operate the aircraft within the limitations of the AFM
- failure to maintain required flight visibility and cloud separation during a visual segment

- failure to maintain required terrain clearance
- failure to comply with minimum descent altitudes
- failure to maintain minimum traffic separation standards
- failure to comply with the hand-over/take-over technique (not applicable to single pilot authorisations)
- failure to safely and consistently apply the elements of NTS1 and NTS2.

If the error is safety critical and the examiner needs to take control or intervene, the flight test must be terminated immediately. Some credits may be given for test items already assessed that are not associated with or relevant to the safety critical event.

Non safety critical items

The second level is where the control of the aircraft is such that the safe outcome of the manoeuvre or procedure is certain, but the flight tolerances have been exceeded or the technique is unsatisfactory. Under these circumstances the flight test may be continued and credits given for successfully completed test items.

The examiner has the discretion to enable the applicant to demonstrate NTS2 TEM to avoid the situation where the error becomes safety critical.

Credits are only valid for one retest.

25.5 Complete (post flight)

25.5.1 Debriefings

The examiner must debrief the applicant and the training provider as soon as practicable after the conclusion of the flight component.

In the event of a fail assessment, in addition to the verbal debriefing, the examiner should ensure sufficient detail is entered into the applicant's training records to allow the training provider to construct a remedial training program.

25.5.2 Flight test administration

At the conclusion of the flight test, the examiner must:

- within 14 days after the day of the test, complete the flight test report and provide a copy of the report to the applicant, training provider and CASA
- within 14 days complete the flight test management system notification requirements.

All items on the test form must be marked to indicate the assessment, with either \checkmark (pass), X (fail), N (not tested) or TR (training records).

Licence entries made by the examiner (if applicable) must be in accordance with the Flight Crew Licensing Manual.